

TWO TIER QDS MAN BASKET

The Two Tier QDS Man basket was designed by JET Group with safety & ease of function in mind. This unit can be utilised as lower basket only or with the addition upper basket. The Two Tier QDS Man Basket is RPEQ Certified, so to guaranty quality for mine site compliance.

The Two Tier QDS Man Basket features internal handrails to prevent hand injuries and an Emergency Stop Valve that is also accessible to the Upper Basket. It also includes self-closing gates and an Emergency Egress ladder. There is a storage compartment for the access ladder for when the Upper Basket is not in use and there are 4 x anchor points (2 x Upper Basket & 2 x Lower Basket).

The Two Tier Man Basket features fork pockets for ease of assembling and dismantling the Upper & Lower Basket and ease of transport.

SUITABLE FOR THE FOLLOWING MACHINES:

Eimco ED7, ED10, EJC130

JUG-A-O Z1060, Z1210

Sandvik LS170, LS190, LS312

Coaltram CT08, CT10, CT13

Caterpillar CL210, CL215

Torque Titan



UPPER & LOWER BASKET ONLY

FEATURES	SPECIFICATIONS
Removable access ladder with storage position	WLL:.....2250KG
4 x Harness and Anchor Points (2 x Upper Basket and 2 x Lower Basket)	Tare Mass:.....2170kg (includes lower basket and ladder)
Emergency Stop Valve accessible from Upper Basket	Dimensions:.....Length:.....2945mm
Fork Pockets for ease of Assembly	Width:.....2200mm
Internal handrails to prevent hand injuries	Height:.....2540mm
Self-closing gates	Floor Area:.....2060mm x 1564mm (Upper Basket)

LOWER BASKET ONLY

FEATURES	SPECIFICATIONS
2 x Harness and Anchor Points	WLL:.....3000KG
Emergency Stop Valve	Tare Mass:.....1460kg
Fork Pockets for ease of Assembly	Dimensions:.....Length:.....2945mm
Internal handrails to prevent hand injuries	Width:.....2200mm
Self-closing gate	Height:.....1648mm
	Floor Area:.....2320mm x 2055mm

JET HIRE

- ★ NDT Tested on an annual basis
- ★ Plant Safety File to be supplied upon Hire
- ★ Risk Assessment to be supplied upon Hire